


## NovoTouch BK752i

True 75" UHD 4K interactive display with wireless collaboration and touch interaction



### Features

#### Hardware

- 75" display with UHD 4K (3,840 × 2,160) resolution for outstanding details and stunning visuals
- 3mm-thick toughened glass for added protection against scratches or screen damage.
- Front bezel USB-A, USB-C ports for quick connection to USB keyboards/mice, memory drives and data
- High-speed Wi-Fi 6 connection
- Dual RJ45 ports for easy Ethernet expansion

#### Software

- Built-in whiteboard and NovoConnect screen sharing Apps to facilitate efficient collaboration in meeting rooms and classrooms.
- Screen annotation and recording tools available for easy content sharing.
- Centralized device management through Remote Manager Cloud or Windows software, simplifying IT administration.

### Specification:

<b>Display</b>	Type/Technology		Backlit D-LED (ADS Panel)
	Panel Size		75"
	Brightness (Typ)		400cd/m2
	Contrast Ratio (Typ)		4000:1
	Native Resolution		4K Ultra-HD (3840 x 2160)
	Viewing Angle (H/V)		178°/178°
	Aspect Ratio		16:9
	Response Time (MS)		6ms (Typ.)
	Refresh Rate (Hz)		60Hz
	Estimated Lifetime (Typ.)		30,000 hours (Min)
	Display Color (Bit)		1.07 billion (10-bit)
Installation Orientation		Landscape	
Daily Operation (Hours/Days)		16/7	
<b>Interactivity</b>	Technology		Infrared Touch
	Touch Points	Writing	10 Point (Standard)
		Touch	20 Point (Standard)
	Accuracy	Finger	±1mm (Over 90% area)
		Passive Pen	±1mm (Over 90% area)
	Touch Resolution		32,768 x 32,768
Surface Protection		3mm Anti-Glare Thick Toughened Glass (Level 7H on Mohs Scale of Mineral Hardness)	
Touch Tools		Finger, Stylus, Glove, Opaque Objects	
<b>Operating System</b>	System Version		Android™ v13.0
	CPU		Multi-Core High-Performance ARM®CPU
	GPU		Mali™ G52
	RAM		4GB DDR4
	Internal Storage		32GB (eMMC Flash) (About 25GB User Availability)
<b>Connectivity</b>	Input	Display	HDMI v2.0 (x3) Side HDMI v2.0 (x1) Front
		Audio	Mic(3.5mm) (x1)
	Output	Display	HDMI-Out v2.0 (x1) (up to 4K@60Hz)
		Audio	Line-Out (3.5mm) (x1), SPDIF-Out (x1)
	Internet		LAN (RJ45) (x2)
	Control		RS232-In (x1)
	Wireless	WiFi	IEEE802.11ax (2.4GHz/5GHz)
		Bluetooth	BT 5.2
	I/R Receiver		Front (x1) (±25° Angle, >8m Distance)
	USB-A	Front	USB 3.0 (x2)
		Side	USB 3.0 (x2), USB 2.0 (x1)
	USB-B	Front	USB Type B (x1) (For Touch Port)
		Side	USB Type B (x1) (For Touch Port)
USB-C	Front	USB-C (x1) (15W charging & display input)	
<b>Expansion</b>	Windows Module (Option)	Standard Intel 80pin OPS (Option)	
<b>Audio</b>	Speakers	18W (x2) (Stereo)	
	Power Supply (Internal)	AC 100 - 240V, 50/60Hz (4.5A)	
<b>Power</b>	Consumption	≤360W	
	Standby Mode	≤0.5W (Standby)	
<b>Physical Characteristics</b>	VESA Mounting (FPMPMI)	800 x 400mm, 4 - M8 × 25mm	
	Mini PC VESA Mount	100 x 100mm	
	Dimension (L x H x D)	1,705.7 x 90.2 x 1,032.3 mm	
	Weight	50kg	
	Color	Silver	
<b>Accessories</b>	Standard	AC Power Cord, Stylus (x2), Remote Control (W/Batteries), Wall Mount Kit, HDMI Cable (3M), Touch Cable (3M) Documentation Kit	
	Optional	LauncherPlus Windows OPS Module – Standard 80pin	

©2024 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.