



Novo NC-X500

Vivitek's Wireless Presentation (x500)



Key Features



Wireless Presentation

at 4K 60fps



Wireless Collaboration

Up to 64 users simultaneously



Flexible Connections

Download our software or use our launcher to share Wirelessly



Remote Management

Manage devices remotely from a central computer
Online software and firmware update



Security

AES-256 encryption, PIN Code for meetings
Settings lock to prevent unauthorized access to device



BYOM

Bring Your Own Meeting by connecting to your AV equipment with NovoConnect



On screen annotation

NovoConnect NC-X500

Wireless Presentation and Collaboration Solution



Product Specification

Storage	Internal : 16 GB (eMMC Flash) External : MicroSD card slot (Up to 32GB) and USB drive	
WiFi	802.11 b/g/n/ac (2.4GHz & 5GHz) 2T2R	
Ethernet (RJ-45)	x1 (10Mbps/ 100Mbps/ 1Gbps)	
Bluetooth (5.0)	Built-in	
HDMI Out	x1 (V2.0) Resolution : 720P @60fps 1920x1080p @60fps 4K @60fps	
Audio Out	x1	
USB port (Host)	x3 (USB 2.0x1, USB 3.0x1, USB-Cx1)	
IR Remote Control	x1	
Kensington Lock	x1	
Operating Temperature	0°~ 40° C; 32°~ 104° F (Ambient)	
Storage Temperature	-20° C ~ 60° C; -4° ~ 140° F (Ambient)	
Power	5V@2A	
Dimensions (W×D×H)	96×105×28 mm (3.8" × 4.13" × 1.10")	
Weight	316g (11.1oz)	
Standard Accessories	AC-DC adaptor USB power cable HDMI Cable IR Remote Control	Wi-Fi antenna Mounting Kit Documentation Kit

Software

OS Supported	Windows 10+, MacOS 10.11+, Android 5.0+, iOS 9+, Chromebook
Mirroring Software	Windows & Mac, iOS, Android, Airplay, GoogleCast and Miracast
Management Software	Remote Manager for Windows and Cloud
Built-in Apps	NT Live (Screen synchronization among multiple units)