

MAXHUB Touch Controller

Model: TCP10M

Transform your meeting spaces with the MAXHUB TCP10M touch controller, designed to seamlessly control MAXHUB IFP/Commercial Display/VideoBar family with leading video conferencing solutions. With one-touch join and easy content sharing, you can enhance collaboration and elevate your meeting experience. Plus, with a simple setup using a single cable routed through the back of the device, installation is a breeze.



High Resolution

10.1" 1920(H)×1080(V)



Touch Screen

10-point capacitive touch recognition



Power Over Ethernet

A single cable carries both power and data to reduce clutter



Cable Free Paring

Connect to your Maxhub Display /VideoBar wirelessly



Sleek Design

Control options are clear and accessible



Compatibility

Compatible with MAXHUB IFP/Commercial Display/VideoBar S10Pro/S15 family

Display

Size	10.1 inch
Resolution	1920 (H) x 1080 (V)
Refreshing Frequency	60Hz
NTSC	55%
Back Light Unit	ELED
Brightness with glass (typ)	280cd/m ²
Life Span	15000 Hours

Operating System

System Version	Android 10.0
RAM	4G
ROM	16G
CPU	A53×4
GPU	Mali-G52

Touch System

Sensing Type	Capacitive touch recognition
Touch Tool	Finger,Passive infrared pen (Optional)
Accuracy	±2mm
Touch Point	10 points touch
Minimum Size	6mm

Microphone (For pairing with host only)

Quantity	2
Distance	0~4m

Bluetooth

Version	5.0
Working Frequency	2.4GHz
Working Distance	0~10m

Wi-Fi

Version	802.11a/b/g/n/ac
Working Frequency	2.4GHz;5GHz
Working Distance	0~10m

Power

Power Requirements	12V3A(Adapter) / 48V0.53A(POE)
Overall Power(Max.)	24W
Standby Power	≤0.5W

I/O Port

USB 2.0	1
RJ45 IN	1
RJ45 OUT	1
DC2.0	1

Physical Specifications

Dimension L×H×D	241.6×157.4×83.2mm
Dimension (package) L×W×H	320×225×145mm
Net Weight	0.85kg
Gross Weight	1.86kg

Speaker

Channel	1.0
Power	1x0.8W

Accessories (included in the package)

RJ45 cable (5m)
Adapter (12V/3A)

Environmental Conditions

Operation Temperature	0 C ~40 C
Operation Humidity	10%~90%RH
Storage Temperature	-20 C ~60 C
Storage Humidity	10%~90%RH
Altitude	Below 5000 meters

Statement

Size and weight vary by configuration and manufacturing process, please refer to the actual product. The product images are for illustrative purposes only and may slightly differ in appearance, colour, size, etc. from the actual product. The description, illustrations, etc. in this document may subject to change in accordance with the latest product specification and performance. Should the above-mentioned change in the document become necessary, the document may be updated without written notice.