3G ULTRA <u>747POE Rackmo</u>unt

Just Add **BPower**

VBS-HDIP-747P0E



All Audio Capable Transmitter

The Just Add Power 3G Ultra 747POE 4-in-1 Rackmount Transmitter supports all lossless audio formats – including Dolby Atmos ®.

Distribute 4K video and lossless audio over Cat5e cable to every zone - along with all the 4K system wide features from the 3G Ultra product line. Mix-and-match with other 3G Ultra Transmitters to distribute any audio format to any zone.

The 747POE 4-in-1 Rackmount Transmitter encodes a 4K or lower-resolution source device into an IP signal and sends it over the network with ultra-low latency and instant switching; along with all the 4K system wide features from the 3G Ultra product line.

Features

Audio	All lossless audio supported - including Dolby Atmos ®	Integrated Endpoint Control	Control endpoints with RS232, IR, and CEC
HDCP 2.2 Support	Display content with HDCP 2.2 copy/content protection on any HDMI screen in system	Scalability	Fully compatible with all 3G Ultra and 2G Omega products
Image Pull	Preview an image from any source or display in any web browser or control system - up to 10 fps		

3G ULTRA 747POE Rackmount



VBS-HDIP-747P0E

Front of Device:

429



All measurements in millimeters (mm)

Back of Device:

429



All measurements in millimeters (mm)

Specifications

Bandwidth	180-500 Mbps	POE	40 watts maximum
		l . .	4 0' 1' 51

O	LIDOD O O	Ports	4 x Gigabit Ethernet
Compliance	HDCP 2.2		4 x HDMI In
	RoHS/FCC/CE		4 v 2 Emm DC222 w/s

	ROHS/FCC/CE		4 x 3.5mm RS232 w/null modem
Dimensions & Weight	429 x 44.5 x 250 mm	Power Supply	Standard Power Cable
•	17" x 1 75" 9 8" in	(included)	IFC 60320 C13/C14

•	17" x 1.75" 9.8" in	(included)	IEC 60320 C13/C14
	(19-inch rack, 1 RU)	, ,	
	3.0 kg / 6.6 lb		

Encryption	Hardware-Based AES 256-bit	Supported	Up to 4096x2160
	Encryption of network video signal	Resolutions	(interlaced & progressive)

Operating Temp 0-60 °C / 32-140 °F